

CmStick

Article-No:
1001-02-100



RoHS compliant
WEEE-Reg-No:
DE 90465365

All dimensions in millimeter.
Subject to change without
notice.



WIBU-SYSTEMS AG
Rueppurrer Strasse 52-54
D-76137 Karlsruhe
Tel: +49-721-93172-0
Fax: +49-721-93172-22
info@wibu.com
www.wibu.com

WIBU
SYSTEMS

Certificates

The CmStick is tested and qualified with the following standards:

■ CE-Conformity | European Certificates

Radiated Emissions according to EN 55022/2003 (DIN VDE 0878 Part22, EN 55022:1998 + A1:2000 + A2:2003.

Immunity according to EN55024 (VDE 0878 part 24): 2003-10; EN 55024:1998 + A1:2001 + A2:2003 against:

Radiated Radio Frequency (RF) and electromagnetic field
Electrostatic Discharge (ESD), air discharge

Conducted Electromagnetic RF

Fast Transient Bursts

DIN EN 61000-3-2 (VDE 0838 part 2):2001-12;
EN 61000-3-2:2000

DIN EN 61000-3-3 (VDE 0838 part 3):2002-05;
EN 61000-3-3:1995 + Corr.: 1997 + A1:2001

■ International Certificates

FCC Part 15, Subpart B / VCCI 2003-04 (Japan)

■ Other Certificates

VDE / GS: VDE-Reg-No. 129382

UL C-UL-US listed I.T.E. Accessory 10WB, E-File 211202

The encryption device is only for use with UL listed PCs (low power system). Meets UL 60950-1 and CSA C22.2 No. 60950-1 Safety of Information Technology Equipment.

Listed on USB Integrators List.

All CmSticks marked as RoHS are fully compliant according to EC Directives 2002/95/EC (RoHS) and 2002/96/EC (WEEE).

SGS testing report CE/2008/B5773, December 2008

Ordering Information

P/N 1001-02-100: CmStick bulk

P/N 1610-5018: Cover with clamp | RAL 5018 ■

Other variants with Individual cases, colors or labels on request.

Description

The CmStick is the heart of the CodeMeter Digital Rights Management system as USB device in a very small and noble case. It contains a SmartCard chip including a secure memory of about 384 kbyte available for storing thousands of licenses. The basic idea of the revolutionary CodeMeter concept is that licenses can be stored for many products even from many different vendors at the same time.

License Options are: Text (description of an entry), Unit Counter (number of runs or actually run time of a license), Activation Time (the license is valid from), Expiration Time (the license is valid until), Usage Period (starts at first time), Feature Map (up to 32 modules or versions), License Quantity (concurrent use / floating network licenses), Protected Data / Extended Protected Data (128x256 bytes read-only data), Hidden Data (128x256 bytes only readable with password; usable as secret/private key), Secret Data (128x256 bytes non-readable, only usable as secret/private key), User Data (unsecured 256 bytes), Customer Owned License Information (256 bytes).

Used algorithms: 128 bit AES, SHA-256, 1024 bit RSA, 224 bit ECC.

The used SmartCard chip contains a random number generator according to FIPS140-1 and fulfills EAL 4+ (Common Criteria certified). The CmStick has a green and a red LED.

Technical Specifications

The CodeMeter technology is covered by US 7.145.297 and other patents.

- **Interface:** Hi-Speed USB 2.0 certified, backward compatible with USB 1.1
- **Data retention:** >10 years @ 100k program/erase cycles
- **Power supply:** 5 V bus-powered, < 60 mA
- **Temperature:** 0...55 degree C, non-condensing
- **MTBF (Mean Time Between Failures):** > 3 Million hours
- **Case/Dimensions:** Noble plastic case, 8 mm x 16 mm x 53 mm, Stick with protective cover: 12 mm x 25 mm x 77 mm
- **Weight:** CmStick 6 g, Cover 8 g
- **Warranty:** 36 months

